

<i>Customer</i>		<i>Date</i>	06/11/23
<i>Project</i>		<i>Engineer</i>	Miroslav Stibor
<i>HEX Type</i>	XB37H-1-36	<i>Contact Person</i>	
<i>Product Code</i>	004H7305	<i>E-mail</i>	
<i>Units Connected</i>	1 (Parallel)		

Calculated Parameters	Unit	Side 1	Side 2
<i>Flow Type</i>		CounterCurrent	
<i>Heat Load</i>	kW	13.95	
<i>Inlet Temperature</i>	°C	50.0	42.6
<i>Outlet Temperature Actual</i>	°C	43.5	48.7
<i>Mass Flow Rate</i>	kg/s	0.57	0.55
<i>Volumetric Flow Rate</i>	L/min	33.33	33.33
<i>Total Pressure Drop</i>	kPa	13.06	9.63
<i>Pressure Drop in Port</i>	kPa	0.73	0.65
<i>Surface Margin</i>	%	0.0	
<i>LMTD</i>	ΔK	1.1	
<i>HTC (Available/Required)</i>	W/m ² ·K	6805 / 6804	
<i>Port Velocity</i>	m/s	1.34	1.34
<i>Shear Stress</i>	Pa	20.09	15.60

Properties of Fluid	Unit	Side 1	Side 2
<i>Fluid</i>		Ethylene glycol (35%)	Water
<i>Liquid Viscosity</i>	mPa·s	1.2519	0.5920
<i>Liquid Density</i>	kg/m ³	1031.9050	990.7283
<i>Liquid Heat Capacity</i>	kJ/kg·K	3.7216	4.1768
<i>Liquid Thermal Conductivity</i>	W/m·K	0.4675	0.6342

Specifications	Unit	Side 1	Side 2
<i>HEX Type</i>		XB37H-1-36	
<i>Number of Plates</i>		36	
<i>Grouping</i>		1*17H/1*18H	
<i>Plate Material</i>		AISI316L	
<i>Effective Area</i>	m ²	1.90	
<i>Brazing Material</i>		Cu	
<i>Volume</i>	l	1.2	1.2
<i>Weight, empty/operating</i>	kg	8.36 / 10.80	
<i>Connection</i>			
<i>Inlet</i>		G 1 Thread	G 1 Thread
<i>Outlet</i>		G 1 Thread	G 1 Thread
<i>Certification/Approval Type</i>			
<i>Minimum Design Temperature</i>	°C	-10.0	
<i>Maximum Design Temperature</i>	°C	180.0	
<i>Maximum Design Pressure</i>	bar(g)	25.0	25.0
<i>H420.2-1.3.21</i>			